

PROPELLER SHAFT & DIFFERENTIAL CARRIER

GI

SECTION PD

MA

EM

LC

MODIFICATION NOTICE:

Service data and specifications (SDS) have been changed.

EC

CONTENTS

FE

SERVICE DATA AND SPECIFICATIONS (SDS)2
Propeller Shaft2

Final Drive.....3

CL

MT

AT

TF

PD

FA

RA

BR

ST

RS

BT

HA

EL

IDX

SERVICE DATA AND SPECIFICATIONS (SDS)

Propeller Shaft

GENERAL SPECIFICATIONS

2WD models

Applied model		Without ABS	With ABS
Propeller shaft model		3S71H	
Number of joints		3	
Coupling method with transmission		Sleeve type	
Types of journal bearings		Solid type (disassembly type)	
Shaft length (Spider to spider)	1st	641 (25.24)	641 (25.24)
	mm (in) 2nd	1,004 (39.53)	978 (38.50)
Shaft outer diameter	1st	75 (2.95)	
	mm (in) 2nd	65 (2.56)	

4WD models

Location		Front	Rear
Propeller shaft model		2F71H	3S80B
Number of joints		2	3
Coupling method with transmission		Flange type	Sleeve type
Types of journal bearings		Solid type (disassembly type)	
Shaft length (Spider to spider)	1st	565 (22.24)	377 (14.84)
	mm (in) 2nd	—	847 (33.35)
Shaft outer diameter	1st	50.8 (2.000)	65.0 (2.559)
	mm (in) 2nd	—	65.0 (2.559)

SERVICE DATA AND SPECIFICATIONS (SDS)

Final Drive

GENERAL SPECIFICATIONS

2WD models

		Standard	Optional
Final drive model		C200	
		2-pinion	LSD
Oil capacity (Approx.)	ℓ (Imp pt)	1.3 (2-1/4)	
Gear ratio		4.375	
Number of teeth	Ring gear	35	
	Drive pinion	8	

4WD models

Front final drive		R180A	
		4-pinion	
Oil capacity (Approx.)	ℓ (Imp pt)	1.3 (2-1/4)	
Rear final drive		Standard	Optional
		H233B	
		4-pinion	LSD
Oil capacity (Approx.)	ℓ (Imp pt)	2.8 (4-7/8)	
Gear ratio		4.875	
Number of teeth	Ring gear	39	
	Drive pinion	8	

GI

MA

EM

LC

EC

FE

CL

MT

AT

TF

PD

FA

RA

BR

ST

RS

BT

HA

EL

IDX