

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive
Technical
DATA
BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

300 ZX (Z31) 1984 to 1990

Type	VG30E
Capacity (cm³) / number of cylinders	2960 / 6
Compression ratio / pressure	9.0 / ≥8.8
Oil pressure	bar [2.9]
Oil temperature	°C –
Valve clearance - inlet	mm 0: Hyd.
Valve clearance - exhaust	mm 0: Hyd.
Firing order	1-2-3-4-5-6
No 1 cylinder position	FR
Thermostat opening temperature	°C 82
Radiator cap pressure	bar 0.78 to 0.98

Fuel system

300 ZX (Z31) 1984 to 1990

Idle speed - manual [auto]	rpm 900±50
Fast idle speed - manual [auto]	rpm –
CO @ idle speed [3000 rpm] - see page VI	% ≤1.0
HC @ idle speed [3000 rpm] - see page VI	ppm ≤1200
CO2 @ idle speed [3000 rpm] - see page VI	% –
O2 @ idle speed [3000 rpm] - see page VI	% –
Carburettor / fuel injection	Nissan ECCS (EFI)
Type / ref	–
Main jet / needle	–
Injection pressure	bar 2.1 @ idle
Pump pressure	bar 2.6
Octane rating	RON 97[R]

Ignition system

300 ZX (Z31) 1984 to 1990

Type	Computerized
Ignition coil	Hitachi CM1T-201
Primary resistance	ohms –
Ballast resistor	ohms –
Voltage - Tmnl 15(+) to earth	V –
Distributor	Hitachi
Points gap (air gap)	mm [0.30 to 0.50]
Dwell angle	° (%) –
Condenser capacity	µF –
Rotation	Anticlockwise
Ignition timing - basic [static]	° Crankshaft @ rpm 10±1 BTDC @ 900±50
V = Vacuum NV = No Vacuum	–
Total ignition advance	° Crankshaft @ rpm –
	° Crankshaft @ rpm –
	° Crankshaft @ rpm –
Centrifugal check.	° Crankshaft @ rpm Computer control
	° Crankshaft @ rpm –
	° Crankshaft @ rpm –
Vacuum range check	mbar Computer control
Maximum vacuum advance	° Crankshaft –
Spark plugs	NGK/Champion
Type	BCPR6ES-11 / RC7YC
Electrode gap	mm 1.00 to 1.10

Electrical system

300 ZX (Z31) 1984 to 1990

Battery	V / CC / RC	12 / 55 or 60Ah
Alternator voltage / full load current / engine rpm		14.1 to 14.7 / – / 2500
Starter motor current / voltage - cranking	A / V	100 / 11 (no load)
- locked	A / V	–

Running gear

300 ZX (Z31) 1984 to 1990

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0
Tyres		
Saloon	Size	210/60x390: 215/60x15
Estate / Van	Size	–
Pressure - front / rear - Saloon	bar	1.9 / 2.3
- Estate / Van	bar	–
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0 to 3.0
Camber		-35' to +55'
Castor		+5°50' to 7°20'
Kling pin inclination		+12°15' to 13°45'
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-1.5 to +2.5
Camber		-1°55' to -25'

Torque wrench settings

300 ZX (Z31) 1984 to 1990

Cylinder head - stage 1	Nm	29
- stage 2	Nm	59, then loosen bolts
Cylinder head - stage 3	Nm	29
- stage 4	Nm	54 to 64'
Big-end bearings	Nm	45 to 54
Main bearings	Nm	90 to 100
Clutch cover	Nm	22 to 29
Flywheel [driveplate]	Nm	98 to 108
Front hubs	Nm	25 to 34
Rear hubs	Nm	294 to 392
Wheel nuts / bolts	Nm	Steel: 78 to 98'
Spark plugs	Nm	20 to 29

Capacities


300 ZX (Z31) 1984 to 1990

Engine oil & filter	litres	4.1
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	7.0
Final drive	litres	2.1
Cooling system	litres	11.0
Fuel tank	litres	77


Notes and Illustrations

OR + 60 to 65°
Alloy: 98 to 118


1: Idle speed 2: CO / Mixture




2960 cm³, 12V



2960 cm³



ECCS



ECCS